

Data sheet EcoMaxX ST2 1-25-6 in UESA Distribution box

| | |
|-------------------------|---|
| Type: | Single phase with separate transformer |
| Power: | 8,0 kVA / 1-phase |
| Nominal current: | 35 A |
| Input voltage: | 230 VAC \pm 10% |
| Dimensions: | 1420 x 320 x 240 mm (H x W x D) / Polyester resin housing for outdoor installation |
| Weight: | 41 kg |
| Protection level: | IP 44 (in housing) |
| Control: | <ul style="list-style-type: none"> ▪ Microcontroller M14 with 16 hours power reserve ▪ Display with 4-button user interface ▪ Status indication via LED ▪ Voltage reduction 10%, 12% or 14% ▪ Mode selection via contacts or internal clock |
| Operation: | <ul style="list-style-type: none"> ▪ soft resistor switch for uninterrupted switching ▪ lamp burn-in time adjustable |
| Safety: | <ul style="list-style-type: none"> ▪ Interlocked relays (electrical und logical) ▪ Voltage monitoring, current monitoring ▪ Cut-out condition according DIN VDE 100 - 410 ▪ Temperature monitoring ▪ Isolated failure signal contact ▪ Automatic internal bypass in case of failure |
| Range of use: | <p>Conventional ballasted lamps:</p> <ul style="list-style-type: none"> ▪ High-pressure mercury-arc lamps ▪ High-pressure sodium-arc lamps ▪ Low-pressure sodium-arc lamps ▪ Mixed lamp systems ▪ Linear (fluorescent) luminaires |
| Tralec Material Number: | G20094a |

Dimensions:

