

Data sheet EcoMaxX ST2 3-16-11 Rack

Type:	3 phase with separate transformers
Power:	11,1 kVA / 3-phase
Nominal current:	16 A per phase
Input voltage:	230 VAC \pm 10%
Dimensions:	1000 x 250 x 135 mm (H x W x D)/ on mounting plate
Weight:	35 kg
Protection level:	IP 00
Control:	<ul style="list-style-type: none"> ▪ Microcontroller M14 with 16 hours power reserve ▪ Display with 4-button user interface ▪ Status indication via LED ▪ Voltage reduction 10%, 12% or 14% ▪ Mode selection via contacts or internal clock
Operation:	<ul style="list-style-type: none"> ▪ soft resistor switch for uninterrupted switching ▪ lamp burn-in time adjustable
Safety:	<ul style="list-style-type: none"> ▪ interlocked relays (electrical und logical) ▪ Voltage monitoring, current monitoring ▪ Cut-out condition according DIN VDE 100 - 410 ▪ Temperature monitoring ▪ Isolated failure signal contact ▪ Automatic internal bypass in case of failure
Range of use:	Conventional ballasted lamps: <ul style="list-style-type: none"> ▪ High-pressure mercury-arc lamps ▪ High-pressure sodium-arc lamps ▪ Low-pressure sodium-arc lamps ▪ Mixed lamp systems ▪ Linear (fluorescent) luminaires
TraleC Material Number:	G20051d

Dimensions:

Front view

